Canon Desktop Solutions - Monochrome Laser Multifunctional and Single Function

Updated March 2020













		4			7
Model	imageCLASS MF543dw	imageCLASS MF449dw	imageCLASS LBP352dn LBP351dn	imageCLASS LBP325dn	imageCLASS LBP228dw
Introduction Date	Dec-19	Apr-20	Apr-16	Oct-19	Sep-19
Supported Functions					
Сору	Std.	Std.	N/A	N/A	N/A
Network Print	Std.	Std.	Std.	Std	Std
Network Scan	Std.	Std.	N/A	N/A	N/A
Fax	Std.	Std.	N/A	N/A	N/A
Send	Std. Color Send	Std. Color Send	N/A	N/A	N/A
Scan to USB/Print from USB	Std.	Std.	N/A	N/A	N/A
Wi-Fi Connectivity	Std.	Std.	N/A	N/A	N/A
Specifications					
Output Speed (BW / Color)	Up to 45 ppm	Up to 40 ppm	Up to 65 ppm Up to 58 ppm	Up to 45 ppm	Up to 40 ppm
First Print Out Time (FPOT)	as fast as 6.0 sec.	as fast as 6.2 sec.	as fast as 7.0 sec. as fast as 7.2 sec.	as fast as 5.6 sec.	as fast as 5.3 sec.
Warm-up Time	14 sec. or less (From Power On)	14 sec. or less (From Power On)	29 sec. or less (From Power On)	30 sec or less (From Power on)	14 sec or less (From Power on)
<u> </u>	4 sec. or less (From Sleep Mode)	4 sec. or less (From Sleep Mode)	12 sec. or less (From Sleep Mode)	3 sec or less (from Sleep Mode)	4 sec or less (from Sleep Mode)
User Interface	5 inch TFT LCD WVGA Color Touch panel	5 inch TFT LCD WVGA Color Touch panel	5-Line LCD Panel	5-Line LCD Panel	5 inch TFT LCD WVGA Color Touch panel
Memory	1GB	1GB	1GB	1GB	1GB
HD Capacity	N/A	N/A	N/A	N/A	N/A
Standard Paper Capacity	650 Sheets (550-Sheet Cassette, 100-Sheet Multipurpose Tray)	350 Sheets (250-Sheet Cassette, 100-Sheet Multipurpose Tray)	600 Sheets (500-Sheet Cassette, 100-Sheet Multipurpose Tray)	650 Sheets (550-Sheet Cassette, 100-Sheet Multipurpose Tray)	350 Sheets (250-Sheet Cassette, 100-Sheet Multipurpose Tray)
Maximum Paper Capacity	2,300 Sheets	900 Sheets	3,500 Sheets	2,300 Sheets	900 Sheets
Paper Weights	16lb. to 32lb. Bond (60 to 120 g/m2)(Cassettes) 16lb. to 73lb. Cover (60 to 199 g/m2) (Multipurpose Tray)	16 lb. Bond to 32 lb. Bond (60 to 120 g/m2) (Cassettes) 16 lb Bond to 60 lb Cover (60 to 163 g/m²) (Multi-Purpose Tray)	16lb. to 32lb. Bond (60 to 120 g/m²)(Cassettes) 16lb. to 53lb. Bond (60 to 199 g/m²) (Multipurpose Tray)	16lb. to 32lb. Bond (60 to 120 g/m2)(Cassettes) 16lb. to 73lb. Cover (60 to 199 g/m2) (Bypass)	16lb. to 32lb. Bond (60 to 120 g/m2)(Cassettes) 16lb. to 60lb. Cover (60 to 163 g/m2) (Multipurpose Tray)
Max. Output Size	8.5" x 14"	8.5" x 14"	8.5" x 14"	8.5" x 14"	8.5" x 14"
Dimensions	19 1/2" x 18 1/4" x 17 3/4"	17 7/8" x 18 1/4" x 15 1/2"	16.4" x 20.9" x 17.3"	16 3/8" x 14 7/8" x 13"	17 1/4" x 14 3/4" x 12 1/4"
Power Requirement/Plug	AC 120 V - 127 V, 7.1 A, 60 Hz	AC 120 V - 127 V, 5.9 A, 60 Hz	120-127V AC / 60Hz / 7.1A/ NEMA 5-15P	AC 120 V - 127 V, 7.0 A, 60 Hz	AC 120 V - 127 V, 5.7 A, 60 Hz
Typical Electricity Consumption (TEC) v3.0			I		
[One Week]	.40 kWh	0.34 kWh	.88 kWh78 kWh	.50 kWh	.33 kWh
Power Consumption	Maximum: 1,430W or less Sleep Mode: 0.9 W or less	Maximum: 1,310 W Sleep Mode: 0.9 W	Maximum: 880 W or less Maximum: 820 W or less Sleep Mode: 20 W or less Sleep Mode: 20 W or less	Maximum: 1,370W or less Sleep Mode: 1.9W or less	Maximum: 1,280W or less Sleep Mode: 0.9W or less
Duty Cycles					
Recommended Monthly Print Volume	2K-7.5K Pages	750 - 4k Pages	5K-20K Pages	2K-7.5K Pages	750 - 4K Pages
Consumables					
Toner Yield**	056 H: 21,000 Pages	057 H: 10k Pages	039 H: 25,000 Pages	20,500 056 H: 21,000 Pages	057 H: 10,000 Pages
Paper Handling Accessories					
Document Feeder & Capacity	50 Sheets	Single Pass DADF / 50 Sheets	N/A	N/A	N/A
Scan Speed (BW/Color, Letter)	Simplex: 38/13 (300 dpi), 21 (600 dpi) Duplex: 71/27 (300 dpi), 35 (600 dpi)	Simplex: 38/13 (300 dpi), 21 (600 dpi) Duplex: 71/27 (300 dpi), 35 (600 dpi)	N/A	N/A	N/A
Output Capacities / Trays	150 Sheets	150 Sheets	Output tray: Approx. 500 sheets Sub-output tray: 100 sheets	N/A	N/A
Printer			Sub-output tray. Too sneets		
Printer Controller(s)	Std. UFR II, PCL6, Adobe® PostScript® 3™	Std. UFR II, PCL6, Adobe [®] PostScript [®] 3 [™]	Std. UFR II, PCL6, Adobe® PostScript® 3™	Std. UFR II, PCL6, Adobe® PostScript® 3 [™]	Std. UFR II, PCL6, Adobe® PostScript® 3™
(Supported PDLs)		Std. UFR II, PCL6, Adobe PostScript 3	Std. UFK II, PCLO, Addibes Postscriptes 5	Std. UFR II, PCL6, Adobe® PostScript® 3	Std. UFR II, PCL6, Adobe® Postscript® 3
Network Interfaces	1000Base-T/100Base-TX/10-Base-T, Wireless LAN (IEEE 802.11 b/g/n), NFC, Wi-Fi Direct Connection	1000Base-T/100Base-TX/10-Base-T, Wireless LAN (IEEE 802.11 b/g/n), Wi-Fi Direct Connection	10/100/1000 Base-T Ethernet	1000Base-T/100Base-TX/	1000Base-T/100Base-TX/10-Base-T, Wireless LAN (IEEE 802.11 b/g/n), Wi-Fi Direct Connection
Other Interfaces	USB 2.0 (Host) x2, USB 2.0 (Device) x1	USB 2.0 (Host) x 3, USB 2.0 (Device) x1	USB 2.0 High Speed	USB 2.0 (Host) x2, USB 2.0 (Device) x1	USB 2.0 (Host) x2, USB 2.0 (Device) x1
Scan / Send Features					
Delivery Options	E-Mail, I-Fax (SMTP, POP3), FTP (TCP/IP), SMB (TCP/IP)	E-Mail, I-Fax (SMTP, POP3), FTP (TCP/IP), SMB (TCP/IP)	N/A	N/A	N/A
Security Features					
Authentication/Access Control	Standard: Department ID, Embedded Universal Login Manager, uniFLOW Online Express Optional: uniFLOW and uniFLOW Online	Standard: Department ID, Embedded Universal Login Manager, uniFLOW Online Express Optional: uniFLOW and uniFLOW Online	Standard: Department ID Optional: uniFLOW	Standard: Department ID Optional: uniFLOW and uniFLOW Online	Standard: Department ID Optional: uniFLOW and uniFLOW Online
Data Security	Standard: Verify System at Startup	Standard: Verify System at Startup	N/A	N/A	N/A
Network Security	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6
Document Security	Standard: Secure Print Optional: Send PDF Security Feature Set	Standard: Secure Print Optional: Send PDF Security Feature Set	Standard: Secure Print Optional: Encrypted Secure Print (with SD CARD-C1 kit)	Standard: Secure Print, Encrypted Secure Print	Standard: Secure Print
Warranty					
Included Warranty	1 Year Limited (Exchange/Carry-in)	1 Year Limited (Exchange/Carry-in)	1 Year Limited (On-Site)	1 Year Limited (Exchange/Carry-in)	1 Year Limited (Exchange/Carry-in)
	1 Year 2 Year	1 Year 2 Year	1 Year 2 Year	1 Year 2 Year	1 Year 2 Year
eCarePAK Extended Service Plans	2 Year 3 Year	2 Year 3 Year	3 Year	2 Year 3 Year	2 Year 3 Year
	4 Year	4 Year	4 Year	4 Year	4 Year
Other Features and Options				···	
Send File Formats	Standard: TIFF, JPEG, PDF(Compact, Searchable) Optional: PDF(Encrypted, Digital Signature)	Standard: TIFF, JPEG, PDF(Compact, Searchable) Optional: PDF(Encrypted, Digital Signature)	N/A	N/A	N/A
Fax Memory			N/A	N/A	N/A
	up to 512 pages ENERGY STAR® Certified, Rated EPEAT® Silver	up to 512 pages ENERGY STAR® Certified, Rated EPEAT® Silver	ENERGY STAR® Certified, Rated EPEAT® Silver	1971	N/A ENERGY STAR® Certified, Rated EPEAT® Silver
Environmental Information	·	· ·	N/A	ENERGY STAR® Certified, Rated EPEAT® Silver	
Accessibility Options	N/A	N/A	IV/A	N/A	N/A
Note: Capacities are based off of 20lb (75g/m2) unless					

Note: Capacities are based off of 20lb (75g/m²) unless otherwise noted.

* Time from device power-on, until copy ready (not print reservation)

** The estimated life is a reference value in the case of usage in a typical office. The actual value varies depending on the customer environment, field operation status, etc.